

EZ-6010 DUCT SEALANT – REDDISH BROWN COLOR

The EZ-6010 is a flammable solvent based product used for sealing air conditioning and heating ducts. It has the same general composition as our EZ-4719, but the viscosity of this product is 120,000 to 140,000 centipoise, while EZ-4719 has a viscosity of approximately 20,000 centipoise. This product is the same as our PA-2084 except this is a reddish-brown color. EZ-6010 is our premium grade U.L. listed duct sealant



New Label Coming Soon

APPLICATIONS

- Sealing sheet metal joint and seam in high or low pressure duct systems.
- Sealing off sheet metal screw and rivets heads.
- Making airtight and watertight all types of galvanized, aluminum or stainless steel sheet metal seams.
- Adhering butted fiberglass duct liner joints to prevent edge pick up by high velocity air.
- Sealing and seaming air systems as used in dryers, air conditioners, etc.

ADVANTAGES

- Forms a tough airtight and watertight seal.
- Flexes with expansion and contraction of the sheet metal.
- Can be applied quickly by caulking gun, trowel, putty knife or heavy brush.
- Bonds to galvanized, stainless steel or aluminum.
- Adds structural strength to the flange or seam.
- A non-hazardous air pollutant

PROPERTIES

Composition:	An oil and water resistant rubber compound which cures into a tough flexible seal. It bonds very well to galvanized, stainless steel or aluminum sheet metal. Once cured it will not flow out of the sealed flange under pressure but will flex with expansion and contraction
Color:	Reddish Brown
Viscosity:	~120,000 cp. to 140,000 cp.
Solids:	~47%
Solvents:	Methyl Ethyl Ketone
Storability:	Store up to 6 months in tightly closed containers.
Service Temperature:	-20°F to 250°
Application and Storage:	Apply at temperatures 40°F to 110°. Store at 0°F to 120° but material should be minimum of 40°F in order to get proper bond
Application Techniques:	Caulk gun, putty knife, trowel or heavy brush
Tack Time:	Tack free for 10 - 15 minutes. Full cure in 1 to 3 days
Open Time:	
Flammability:	Wet – Flammable. Dry – slow burning
Coverage Per Gallon:	1/8" bead – 130 to 150 lineal feet 1/4" bead – 30 to 60 lineal feet

Not recommended for exposed outdoor use

Color



Application Methods

