

PA-4084 WATER BASED DUCT SEALANT

The PA-4084 is a 100 percent solvent free product used for sealing air conditioning and heating ducts. It is an extremely fast drying, odor free, environmentally friendly product. PA-4084 is a superior bond and is U.L listed. We consider this the premium water based duct sealant.



APPLICATIONS

- Sealing sheet metal joints and seams in high or low pressure duct systems.
- Sealing and seaming air passages in dryers, air conditioners, and industrial air processing units.
- Closing holes and sealing screw and rivet heads in sheet metal.

ADVANTAGES

- Forms an air-tight and water-tight seal which is tough and strong.
- Flexes with expansion and contraction of the sheet metal.
- Excellent bond to aluminum, galvanized sheet or stainless steel.
- Can be applied quickly by caulking gun, putty knife, trowel or heavy brush.
- Gray color blends well with either aluminum or galvanized metal.
- Adds structural strength to the flange or seam.
- Will not drip or sag.
- Mild odor.

PROPERTIES

Color:	Gray
Viscosity:	~100,000 cp. to 150,000 cp.
Solids:	~62%
Solvents:	Cleanup with hot water while material is still wet.
Storability:	6 months in tightly closed containers, ship and store above freezing.
Service Temperature:	0°F to 190°F will not support mildew growth
Application and Storage:	40°F to 100°F keep from freezing
Weight per Gallon:	9 pounds per gallon
Application Techniques:	
Tack time:	Tack free for 1 to 4 hours depending on weather conditions. Complete drying time is 1 to 2 days at room temperature.
Flammability:	Non-Flammable solvent free

Not recommended for exposed outdoor use

Color



Application Methods



24Y3
R-14526